





HAZARD RATING 4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT 0=INSIGNIFICANT	<b>HEALTH</b>	<b>1</b>	SAFETY DATA SHEET HARRIS NO. PPLHA0400 <b>HARRIS GREEN STARSEAL</b> <b>1500 RELEASE</b>
	<b>FLAMMABILITY</b>	<b>0</b>	
	<b>REACTIVITY</b>	<b>0</b>	

**SECTION I - GENERAL INFORMATION**

<b>PRODUCT IDENTIFICATION:</b>	
<b>HARRIS GREEN STARSEAL 1500 RELEASE</b>	
<b>VOC CONTENT:</b>	<25 GRAMS/LITER OR <0.21 #/GAL
<b>CATEGORY:</b>	FORM RELEASE
<b>COMMON NAME:</b>	FORM RELEASE WATER EMULSION
<b>MANUFACTURER:</b>	<b>A.H. HARRIS &amp; SONS, INC.</b>
<b>ADDRESS</b>	433 S. MAIN ST. SUITE 202 W. HARTFORD CT 06110
<b>TELEPHONE NO:</b>	860-261-9500
<b>CHEMTREC NO:</b>	800.424.9300
<b>PREPARED:</b>	FEBRUARY 1997
<b>UPDATED:</b>	NOVEMBER 2012
<b>PREPARED BY:</b>	DARRY F. MANUEL , PRESIDENT

**SECTION II - HAZARD IDENTIFICATION**

<b>DOT SHIPPING NAME:</b>	
UN ID NUMBER / SHIPPING NAME / HAZARD CLASS / PKG GROUP IN CONTAINERS LESS THAN AND GREATER THAN 119 GALS: IN ALL MODES OF DOMESTIC AND INTERNATIONAL TRANSPORTATION (NON-REGULATED)	
<b>HEALTH AND SAFETY:</b>	
USE WITH ADEQUATE VENTILATION. DO NOT INDUCE VOMITING IF SWALLOWED. USE OF SOLVENT RESISTANT GLOVES, GOGGLES AND OTHER PROTECTIVE CLOTHING IS ADVISED WHEN HANDLING THIS PRODUCT. <b>KEEP FROM FREEZING.</b>	
	

**SECTION III HAZARDOUS INGREDIENTS**

MATERIAL OR COMPONENTS	%	HAZARD DATA	UN NUMBER
WATER SOLUTION OF RELEASE AGENTS	94-98%	NO TLVs OR HAZARDOUS INGREDIENTS	NONE
RELEASE AGENTS	<5%	NONE	NONE

**SECTION IV FIRST AID MEASURES**

**HEALTH HAZARD DATA HAZARD CLASSIFICATION BASIS FOR CLASSIFICATION SOURCE**

**ROUTES OF EXPOSURE:**

<b>INHALATION:</b>	THIS PRODUCT MAY CREATE BREATHING DIFFICULTIES. DIZZINESS, LIGHTHEADEDNESS, HEADACHES WHEN WORKING IN AREAS WITH HIGH VAPOR CONCENTRATION.
<b>SKIN CONTACT:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.
<b>SKIN ABSORPTION:</b>	THIS PRODUCT MAY CAUSE SKIN IRRITATION UPON PROLONGED OR REPEATED CONTACT.
<b>EYE CONTACT:</b>	THIS PRODUCT MAY BE AN EYE IRRITANT.
<b>INGESTION / INHALATION</b>	SMALL AMOUNTS OF LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHOPNEUMONIA OR PULMONARY EDEMA. DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.
<b>EFFECTS OF OVEREXPOSURE:</b>	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS. LIQUIDS MODERATELY IRRITATING ON SKIN AND EYES.
<b>ACUTE OVEREXPOSURE:</b>	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS: MODERATE IRRITATION BY LIQUID TO SKIN AND EYES. PROLONGED CONTACT ON THE SKIN WILL CLAY AND DEBAT THE SKIN POSSIBLY CAUSING DERMATITIS.

**EMERGENCY AND FIRST AID PROCEDURES:**

<b>EYES:</b>	FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEEK IMMEDIATE MEDICAL ATTENTION.
<b>SKIN:</b>	WASH WITH SOAP AND LARGE QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF SKIN IRRITATION DEVELOPS AND PERSISTS.
<b>INHALATION:</b>	MOVE TO LOCATION FREE FROM VAPORS. IF BREATHING STOPS, BEGIN ARTIFICIAL RESPIRATION AND SEEK IMMEDIATE MEDICAL ATTENTION.
<b>INGESTION:</b>	DO NOT INDUCE VOMITING; SEEK IMMEDIATE MEDICAL ATTENTION.

## SECTION V FIREFIGHTING MEASURES

<b>EXTINGUISHING MEDIA:</b>	FIRES INVOLVING THIS PRODUCT MAY BE CONTROLLED BY <b>REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICALS OR WATER SPRAY</b> . WATER MAY BE USED TO REDUCE THE RATE OF BURNING AND FOR COOLING PURPOSES
<b>GENERAL HAZARD:</b>	<b>"EMPTY" CONTAINERS</b> RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR PROPERLY DISPOSED OF.
<b>UNUSUAL FIRE AND EXPLOSION HAZARD:</b>	VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. IF STORAGE CONTAINERS ARE EXPOSED TO EXCESSIVE HEAT, OVER PRESSURIZATION OF THE CONTAINERS CAN RESULT.
<b>SPECIAL FIRE FIGHTING PROCEDURES</b>	THE USE OF <b>SELF-CONTAINED BREATHING APPARATUS</b> WITH FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE SHOULD BE PROVIDED FOR FIRE FIGHTERS IN BUILDINGS OR CONFINED AREAS WHERE THIS PRODUCT IS STORED. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT <b>COOL WITH WATER SPRAY</b> IN ORDER TO PREVENT PRESSURE BUILD UP. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES.

## SECTION VI ACCIDENTAL RELEASE MEASURES

<p><b>STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:</b> ELIMINATE SOURCES OF IGNITION (FLARES, FLAMES, PILOT LIGHTS, ELECTRICAL SPARKS). PREVENT ADDITIONAL DISCHARGE OF MATERIAL; IF POSSIBLE TO DO SO WITHOUT HAZARD. FOR SMALL SPILLS, IMPLEMENT CLEANUP PROCEDURES. FOR LARGE SPILL, IMPLEMENT CLEAN UP PROCEDURES AND, IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. DIKE SPILL AREA WITH SAND OR EARTH TO CONTAIN SPILLED LIQUID AND PREVENT SPREADING. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID CAN BE TAKEN UP ON SAND, EARTH, FLOOR ABSORBENT, OR WITH ANOTHER SUITABLE ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS. CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO EPA, FEDERAL, STATE, AND LOCAL DISPOSAL REGULATIONS.</p>
--

## SECTION VII HANDLING AND STORAGE

<p><b>PRECAUTIONARY STATEMENTS:</b> PERSONNEL SHOULD AVOID INHALATION OF VAPORS. PERSONAL CONTACT WITH THE PRODUCT SHOULD BE AVOIDED. SHOULD CONTACT BE MADE, REMOVE SATURATED APPAREL AND FLUSH AFFECTED BODY AREAS WITH WATER. CLOTHING MUST BE WASHED AND DRIED BEFORE REUSE. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE (VAPOR, LIQUID AND/OR SOLID). ALL HAZARD PRECAUTIONS GIVEN IN THIS DATA SHEET MUST BE OBSERVED.</p>
<p><b>FIRE FIGHTING:</b> WATER MAY BE HELPFUL IN KEEPING ADJACENT CONTAINERS COOL. PERSONNEL SHOULD AVOID INHALATION OF VAPORS.</p>
<p><b>OTHER HANDLING AND STORAGE REQUIREMENTS:</b> STORE AND USE IN WELL VENTILATED AREA, EQUIVALENT TO FRESH AIR. KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS. STORE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. DO NOT STORE OR CONSUME FOOD, DRINK, OR TOBACCO IN AREAS WHERE THEY MAY BECOME CONTAMINATED WITH THIS MATERIAL. KEEP AWAY FROM HIGH TEMPERATURES, OPEN FLAMES, SPARKS, SOURCES OF IGNITION, ETC. USE WITH EXPLOSION PROOF EQUIPMENT IS HIGHLY ADVISABLE.</p>

## SECTION VIII EXPOSURE CONTROLS / PERSONAL PROTECTION

<p><b>VENTILATION REQUIREMENTS:</b> LOCAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO KEEP PRODUCT VAPOR CONCENTRATIONS WITHIN SPECIFIED TIME-WEIGHTED TLV RANGES. IF LOCAL VENTILATION PROVES INADEQUATE TO MAINTAIN SAFE VAPOR CONCENTRATIONS, SUPPLEMENTAL LOCAL EXHAUST MAY BE REQUIRED. OTHER SPECIAL PRECAUTIONS SUCH AS RESPIRATORY MASKS OR ENVIRONMENTAL CONTAINMENT DEVICES MAY BE REQUIRED IN EXTREME CASES.</p>
<p><b>RESPIRATORY (SPECIFY IN DETAIL):</b> THE USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR CONCENTRATION ABOVE THE TIME WEIGHTED TLV: USE OF OSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK OR AIR-PACK. CHEMICAL CARTRIDGE RESPIRATOR: HALF MASK ORGANIC VAPOR CARTRIDGE. FULL FACE ORGANIC VAPOR CARTRIDGE IF EYE PROTECTION IS NEEDED.</p>
<p><b>EYES:</b> CHEMICAL GOGGLES AND/OR FACE SHIELD ARE RECOMMENDED TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY.</p>
<p><b>GLOVES:</b> THE USE OF IMPERMEABLE GLOVES IS ADVISED TO PREVENT SKIN IRRITATION IN SENSITIVE INDIVIDUALS. IMPERVIOUS GLOVES, (CHEMICAL RESISTANT) SUCH AS NEOPRENE, LATEX OR PVA.</p>
<p><b>OTHER CLOTHING AND EQUIPMENT:</b> TO PREVENT BODY CONTACT, IMPERVIOUS CLOTHING AND BOOTS ARE RECOMMENDED. IMPERVIOUS APRONS AND HELMETS (HEAD COVER) ARE RECOMMENDED WHEN WORKING WITH THIS PRODUCT. THE AVAILABILITY OF EYE WASHES AND SAFETY SHOWERS IN WORK AREAS IS RECOMMENDED.</p>

## SECTION IX PHYSICAL / CHEMICAL CHARACTERISTICS

<b>BOILING POINT: (760mmHg)</b> 100°C / 212°F (WATER)	<b>MELTING/FREEZING POINT:</b> 0°C / 32°F (WATER)
<b>VAPOR PRESSURE:</b> 17.5 mmHg@68°F/20°C (WATER)	<b>VAPOR DENSITY (AIR=1):</b> = WATER
<b>SOLUBILITY IN H2O % BY WT:</b> SOLUBLE	<b>% VOLATILES BY VOL:</b> 94-98%
<b>EVAPORATION RATE (BuAc=1):</b> SLOW 0.3 (WATER)	<b>SPECIFIC GRAVITY (H2O=1)</b> 1.0 =WATER
<b>pH (AS IS):</b> 7.5 – 8.0	<b>pH (1% SOLN):</b> N/A
<b>APPEARANCE AND ODOR:</b>	CLEAR LIQUID WITH NO ODOR
<b>FLASH POINT:</b> (TEST METHOD)	<b>NONE (WATER)</b>
<b>AUTOIGNITION TEMP:</b>	NONE (WATER)
<b>FLAMMABLE LIMITS IN AIR, % BY VOL:</b>	NONE (WATER)

## SECTION X STABILITY AND REACTIVITY

<b>CONDITIONS CONTRIBUTING TO INSTABILITY:</b>	THIS PRODUCT IS STABLE.
<b>INCOMPATIBILITY:</b>	THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS OR BASES, AND SELECTED AMINES.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE, AND UNIDENTIFIED ORGANICS.
<b>CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION:</b>	N/A WILL NOT OCCUR

**SECTION XI TOXICOLOGICAL INFORMATION**

<b>ACUTE HEALTH HAZARD</b>	INGESTION	LD50: 200-2,000 mg.kg SPECIES: RAT
	INHALATION	NO DATA IS AVAILABLE ON THE PRODUCT ITSELF
	SKIN	NO DATA IS AVAILABLE ON THE PRODUCT ITSELF
	EYE IRRITATION/ COROSION	SEVERE EYE IRRITATION
	ACUTE DERMAL IRRITATION/CORROSION	SEVERE SKIN IRRITATION

**SECTION XII ECOLOGICAL INFORMATION**

<b>ECOTOXICITY EFFECTS</b>	AQUATIC TOXICITY	(96HR): <1 mg/ml SPECIES: FISH
	TOXIC TO ORGANISMS	NO DATA AVAILABLE
<b>PERSISTENCE AND DEGRADABILITY</b>	MOBILITY	NO DATA AVAILABLE
	BIOACCUMULATION	NO DATA IS AVAILABLE ON THE PRODUCT ITSELF.

**SECTION XIII DISPOSAL CONSIDERATIONS**

AQUATIC TOXICITY (E.G. 96 HR. TLM): DO NOT DISCHARGE THIS PRODUCT INTO PUBLIC WATERS OR WATERWAYS UNLESS AUTHORIZED BY A NATIONAL POLLUTION DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT ISSUED BY THE ENVIRONMENTAL PROTECTION AGENCY (EPA).

**WASTE DISPOSAL METHOD:** IF POSSIBLE, PUMP TO CONTROLLED CONTAINMENT AREA. ABSORB ON CLAY OR SAND. DISPOSE OF IN COMPLIANCE WITH EPA, FEDERAL, STATE, AND LOCAL REGULATIONS. TREATMENT TRANSPORTATION AND DISPOSAL MUST BE IN COMPLIANCE WITH EPA FEDERAL, STATE, AND LOCAL REGULATIONS UNDER THE RESOURCES CONSERVATION AND RECOVERY ACT (RCRA, 40 CFR 261). TYPICALLY CONTROLLED BURNING, INCINERATION OR APPROVED LAND FILL SITES ARE AVAILABLE.

**SECTION XIV TRANSPORTATION INFORMATION**

Governing Body	Mode	UN Number	Proper Shipping Name	Hazard Class	Packing Group
DOT	GROUND	NON REGULATED	NON REGULATE D	NON REGULATE D	NA
IATA	AIR	NON REGULATED	NON REGULATE D	NON REGULATE D	NA
IMDG	OCEAN	NON REGULATED	NON REGULATE D	NON REGULATE D	NA
<b>MARINE POLLUTANT:</b>	THIS PRODUCT DOES NOT CONTAIN A MATERIAL. ON THE MARINE POLLUTANTS TABLE (HMT 172.101 APPENDIX B)				

**SECTION XV REGULATORY INFORMATION**

**TSCA:** THE SOLVENT PORTION OF THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AS A UVCB (UNKNOWN, VARIABLE COMPOSITION OR BIOLOGICAL) CHEMICAL AT CAS REGISTRY NUMBER N/A

**CERCLA:** IF THE REPORTABLE QUANTITY OF THIS PRODUCT IS ACCIDENTALLY SPILLED, THE INCIDENT IS SUBJECT TO THE PROVISIONS OF THE COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA) AND MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER BY CALLING 1-800-424-8802 or 202-426-2675.

**NO REPORTABLE SPILL QUANTITY (RQ) HAS BEEN ESTABLISHED FOR THIS PRODUCT**

**SARA TITLE III:** UNDER THE PROVISIONS OF TITLE III, SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND RE-AUTHORIZATION ACT, THIS PRODUCT IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: ACUTE HEALTH HAZARD

**ADDITIONAL REGULATORY CONCERNS:** (FEDERAL, FDA, USDA, CPSC, STATE, OTHER) FEDERAL / FDA / USDA:

**MARINE POLLUTANTS:** NO. THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE MARINE POLLUTANTS TABLE (HMT 172.101 Appendix B).

**CALIFORNIA PROP 65:** WARNING: This product contains chemicals known to the state of California to cause cancer or birth defects or other reproductive harm. (Epichlorohydrin, Ethylbenzene, Crystalline Silica particles of respirable size)

**CERCLA / RQ: NONE ESTABLISHED.** THIS PRODUCT DOES NOT CONTAIN A MATERIAL ON THE RQ TABLE (HMT 172.101 Appendix A):

**TSCA:** IS THIS PRODUCT, OR ALL ITS INGREDIENTS, BEING CERTIFIED FOR INCLUSION ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY OF CHEMICAL SUBSTANCES? **YES**

**SECTION XVI OTHER INFORMATION**

PREPARED BY	DARRYL MANUEL / PRESIDENT
COMPANY:	VEXCON CHEMICALS, INC.
ADDRESS:	7240 STATE RD., PHILA., PA 19135 USA
THE INFORMATION PROVIDED IN THIS MATERIAL SAFETY DATA SHEET HAS BEEN OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. VEXCON PROVIDES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN.	

<b>HMIS HAZARD RATINGS:</b>			<b>KEY</b>
THIS INFORMATION IS FOR PEOPLE TRAINED IN: NATIONAL PAINT AND COATINGS ASSOCIATIONS (NPCA) HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) NATIONAL FIRE PROTECTION ASSOCIATION (NFPA 704) IDENTIFICATION OF FIRE HAZARDS OF MATERIALS			
<b>HARRIS GREEN STARSEAL 1500 RELEASE</b>	<b>NPCA-HMIS</b>	<b>NFPA 704</b>	4 -- SEVERE
<b>HEALTH</b>	<b>1</b>	<b>1</b>	2 -- MODERATE
<b>FLAMMABILITY</b>	<b>0</b>	<b>0</b>	1 -- SLIGHT
<b>REACTIVITY</b>	<b>0</b>	<b>0</b>	0 -- MINIMAL